NSN 5905-00-984-6124

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-984-6124

excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	empurature Coefficient Of Resistance In Ppm Per Deg Celsius:
2.150 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+150.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, executudes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: Demilitarization:	500.0/+200.0
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 15.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+150.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	lectrical Resistance:
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+150.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	.150 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/±150.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	esistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+150.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+150.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	mbient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+150.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	0.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+150.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	mbient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	50.0
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	empurature Range Of Tempurature Coefficient In Deg Celsius:
Hermetically sealed Terminal Type: Wire lead Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	S5.0/+150.0
Terminal Type: Wire lead Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	closure Method:
Wire lead Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	ermetically sealed
Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	erminal Type:
0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	/ire lead
Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	ody Diameter:
O.750 inches Power Dissipation Rating In Watts: O.500 free air Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	.250 inches
Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	ody Length:
O.500 free air Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	.750 inches
Style Designator: Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	ower Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	.500 free air
Test Data Document: 18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	tyle Designator:
18876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	xial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	est Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization:	8876-9002953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization:	xcludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization:	helf Life:
 Demilitarization:	/a
	nit Of Measure:
No	emilitarization:
No	0
Fiig:	iig:
A001a0	001a0