## NSN 5905-00-984-8895

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-984-8895

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.9688 inches
Pilot Length:
0.0620 inches
Overall Length:
1.094 inches
Undercut Diameter:
0.975 inches
Undercut Width:
0.0620 inches
Body Diameter:
1.062 inches
Shaft Diameter:
0.1248 inches
Shaft Length:
0.344 inches
Body Length:
0.750 inches
Overall Diameter:
1.250 inches
Mounting Lip Diameter:
1.0620 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
100.0 kilohms single section

Power Dissipation Rating Per Section In Watts: 2.0 free air single section

## NSN 5905-00-984-8895

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section in Percei
-5.0/+5.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0