Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-984-8896

1

Body Style:

Rectangular w/mounting holes

Reliability Indicator:

Not established

**Terminal Length:** 

1.500 inches

Mounting Hole Diameter:

0.078 inches

Shaft Diameter:

0.060 inches

Shaft Length:

0.030 inches

Body Length:

## 0.500 inches

**Body Width:** 

0.195 inches

Body Height:

0.500 inches

Shaft Style:

Round

Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

15120.0

**Center To Center Distance Between Terminals:** 

0.282 inches

Lateral Distance Between Mounting Hole Centers:

0.520 inches

**Mounting Facility Quantity:** 

2

Terminal Location: Lower adjacent side single row

## Mounting Method:

Terminal and unthreaded hole

Features Provided:

Humidity proof

**Electrical Resistance Per Section:** 

50.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

15120.0



| Center To Center Distance Between Center Terminal And Outside Terminal:     |
|---|
| 0.141 inches  |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 150.0 single section  |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:   |
| -50.0/+50.0 single section  |
| Power Dissipation Rating Per Section In Watts:                              |
| 1.0 free air single section   |
| Resistance Tolerance Per Section In Percent:                                |
| -5.0/+5.0 single section  |
| Actuator Travel Control Feature:  |
| Clutch  |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:         |
| 50.0 single section   |
| Standard Taper Curve Per Section:   |
| A single section  |
| Special Features:   |
| Allen head screw adjustment   |
| Terminal Type And Quantity:   |
| 3 pin   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A002a0  |
|   |
|   |
|   |
|   |