NSN 5905-00-985-4830

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-985-4830

20.04-20.0 Electrical Resistance: 2.610 kilohms Resistance Tolerance in Percent: 1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 45.0 Fempurature Range Of Tempurature Coefficient in Deg Celsius: 65.04-145.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: 80.05 sold established 80.05 Diameter: 9.250 inches 80.050 Length: 9.0500 inches 90.000	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Forminal Type: Wire lead Reliability Indicator: Not established Body Length: 1.0250 inches Body Length: 1.0500 inches Power Dissipation Rating In Watts: 1.150 free air Skyle Designator: 2.250 inches Body Length: 1.349-milr33/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: 1/42 Jilt Of Measure:	-20.0/+20.0
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 165.0/+145.0 Fempurature Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established 30dy Diameter: 1.250 inches 30dy Length: 1.500 inches Power Dissipation Rating In Watts: 1.501 inches 1.504 resiance are are are are are are are all the second of the seco	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 45.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Attention Body Diameter: 1.250 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 1.500 inches Power Dissipation Rating In Watts: 1.500 inches Reliability Designator: Avail terminal each end Test Data Document: 131349-militaryian specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Jint Of Measure:	2.610 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 165.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 1.250 inches Body Length: 1.050 inches Power Dissipation Rating In Watts: 1.515 free air Style Designator: Axial terminal each end Test Data Document: 18749-milr39/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Va Joint Of Measure: - Demilitarization: No Pilig:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 165.04:145.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 1.250 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 1.510 free air Style Designator: Exist I terminal each end Test Data Document: 184349-milr3/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Va Juit Of Measure: - Demilitarization: No	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/4145.0 Tempurature Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Axial terminal each end Test Data Document: 181349-miliga?13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Va Joint Of Measure: - Demilitarization: No	Ambient Tempurature In Deg Celsius At Full Rated Power:
Pempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 nclosure Method: Encapsulated Perminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: xixial terminal each end Rest Data Document: 91349-milr93/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: - Demilitarization: No	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 nclosure Method: 6.ncapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr93/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: - Demilitarization: No Figig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Xxial terminal each end Fest Data Document: 81349-militg3/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: V/a Jnit Of Measure: - Demilitarization: No Filig:	145.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr93/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: V/a Juit Of Measure: - Demilitarization: No Filig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Nire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Axial terminal each end Fest Data Document: 181349-milr93/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: Demilitarization: No Piig:	-65.0/+145.0
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr93/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: Via Unit Of Measure: Demilitarization: No Period of the stable of the	Inclosure Method:
Action of Measure: Action	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Byte Designator: Axial terminal each end Fest Data Document: 81349-millr93/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: - Demilitarization: No Signature Power Dissipation Signature Stypical ("average", "", etc.).	Terminal Type:
Not established Body Diameter: Diagony Diameter: Diagony Diameter: Diagony Length: District Rating In Watts: Diagony Dissipation Rating In Watts: Diagony Diagony Diagony Diagony Diagony Dia	Wire lead
30dy Length: 0.250 inches 30dy Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Avail terminal each end Fest Data Document: 81349-milr93/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Reliability Indicator:
2.250 inches 3.30dy Length: 2.500 inches 2.5	Not established
Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr93/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization: No	Body Diameter:
Power Dissipation Rating In Watts: 0.150 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr93/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Junit Of Measure: - Demilitarization: No	0.250 inches
Power Dissipation Rating In Watts: 0.150 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr93/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	Body Length:
Style Designator: Axial terminal each end Fest Data Document: 81349-milr93/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No Filig:	0.500 inches
Style Designator: Axial terminal each end Fest Data Document: 31349-milr93/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	Power Dissipation Rating In Watts:
Axial terminal each end Fest Data Document: 81349-milr93/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.150 free air
Fest Data Document: 81349-milr93/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formative excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	Style Designator:
81349-milr93/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-milr93/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Shelf Life: N/a Jnit Of Measure: - Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Jnit Of Measure: - Demilitarization: No Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: - Demilitarization: No Fiig:	Shelf Life:
- Demilitarization: No Fiig:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Filg:	Demilitarization:
	No
	Fiig:
1001a0	A001a0