Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-985-5416

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Overall Length:**

1.375 inches

#### Body Diameter:

1.062 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.500 inches

#### Mounting Bushing Length:

# 0.250 inches

**Body Length:** 

0.875 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

335.0

Nonturn Device Location:

At 9 oclock

**Nonturn Device Radius:** 

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

**Electrical Resistance Per Section:** 

1.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

350.0



#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

# **Actuator Travel Control Feature:**

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0