

NSN 5905-00-985-5937 Nonprecision Wire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-00-985-5937 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.082 inches **Body Diameter:** 1.680 inches **Shaft Diameter:** Between 0.248 inches and 0.251 inches **Shaft Length:** Between 0.578 inches and 0.672 inches **Mounting Bushing Length:** Between 0.453 inches and 0.547 inches **Body Length:**

1.410 inches

Overall Diameter: 2.260 inches **Shaft Style:**

Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:**

40.00 inch-ounces **Maximum Stop Torque:**

240.00 inch-ounces **Nonturn Device Location:**

At 12 oclock

Nonturn Device Radius:

Between 0.485 inches and 0.515 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

NSN 5905-00-985-5937

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
2.5 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 275.0 and 305.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section
Power Dissipation Rating Per Section In Watts:
25.0 heat sink single section
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
31349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
31349-mil-r-22/3 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig: