

View Online at https://aerobasegroup.com/nsn/5905-00-985-5978

# Section Quantity: 1 Body Style: Cylindrical bushing mounted Reliability Indicator:

Not established

**Overall Length:** 

Between 1.776 inches and 1.848 inches

#### **Body Diameter:**

Between 0.859 inches and 0.891 inches

Shaft Diameter:

0.250 inches

Shaft Length:

Between 0.796 inches and 0.828 inches

#### Mounting Bushing Length:

Between 0.296 inches and 0.328 inches

**Body Length:** 

Between 0.980 inches and 1.020 inches

#### **Overall Diameter:**

1.063 inches

Shaft Style:

Round, slotted

## **Contact Arm Electrical Off Position:**

Fully ccw-cw

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

Between 3600.0 and 3610.0

## Maximum Starting Torque:

0.60 inch-ounces

#### Maximum Stop Torque:

48.00 inch-ounces

#### Nonturn Device Location:

At 7 oclock

#### Nonturn Device Radius:

Between 0.280 inches and 0.300 inches

#### Shaft End Play:

0.005 inches

## Shaft Runout:

0.002 inches

# Lateral Runout:

0.005 inches



Pilot Diameter Runou	f-
0.002 inches	
Shaft Radial Play:	
0.003 inches	
	In Dog Angular Potation
	In Deg Angular Rotation:
1.0 Screw Thread Diamet	
	er.
0.375 inches	Decimeter
Screw Thread Series	Designator:
Unef	
Screw Thready Qty P	er Inch (tpi):
32.0	
Terminal Location:	
51	er less than half the circumference
Mounting Method:	
Standard bushing w/sh	
Electrical Resistance	
500.0 ohms single sect	
Rotary Actuator Trave	
Between 3600.0 and 3	
-	Tolerance Per Section:
-0.20/+0.20 single sect	
-	e In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section	
Power Dissipation Ra	ting Per Section In Watts:
2.0 free air single section	
Function Conformity	Per Section:
Single section indepen	dent linearity
Resistance Tolerance	Per Section In Percent:
-3.0/+3.0 single section	1
Actuator Travel Contr	ol Feature:
Stops	
Function Characteris	tic Per Section:
Single section linear	
Tempurature Coeffici	ent Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single sect	ion
Ambient Tempurature	e In Deg Celsius Per Section At Full Rated Power:
70.0 single section	
Terminal Type And Q	uantity:
3 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	

---



Demilitarization:

No

Fiig:

A002a0