

View Online at <https://aerobasegroup.com/nsn/5905-00-985-6203>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Overall Length:

Between 1.290 inches and 1.350 inches

Terminal Length:

Between 0.120 inches and 0.180 inches

Overall Height:

Between 0.220 inches and 0.290 inches

Overall Width:

Between 0.160 inches and 0.220 inches

Mounting Hole Diameter:

0.088 inches

Shaft Diameter:

Between 0.100 inches and 0.120 inches

Shaft Length:

Between 0.040 inches and 0.100 inches

Body Length:

Between 1.220 inches and 1.280 inches

Body Width:

Between 0.160 inches and 0.220 inches

Body Height:

Between 0.290 inches and 0.350 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

7920.0

Maximum Starting Torque:

7.50 inch-ounces

Lateral Distance Between Mounting Hole Centers:

Between 0.990 inches and 1.010 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

5.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

7920.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0/+70.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Clutch

Criticality Code Justification:

Zzzy

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire loop

Reference Number Differentiating Characteristics:

As differentiated by navord od42046

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A002a0