## NSN 5905-00-987-6033

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-987-6033 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established First Flat Length: 0.438 inches Flat Height: 0.217 inches **Body Diameter:** 2.281 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.906 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.938 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 340.0 **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef

Screw Thready Qty Per Inch (tpi):
32.0

Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
25.0 ohms single section
Rotary Actuator Travel In Angular Deg:
340.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
350.0 single section

## NSN 5905-00-987-6033

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
50.0 free air single section
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No