## NSN 5905-00-987-9832

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-987-9832 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.0000 inches Pilot Length: 0.1870 inches **Undercut Diameter:** 1.000 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 1.125 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Body Length:** 1.000 inches **Mounting Lip Diameter:** 1.1250 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Maximum Starting Torque:** 0.50 inch-ounces **Maximum Running Torque:** 0.50 inch-ounces **Shaft End Play:** 

0.005 inchesShaft Runout:0.002 inches

## NSN 5905-00-987-9832

Precision Wire Wound Variable Resistor - Page 2 of 2



Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Rotary Actuator Travel In Angular Deg:
320.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A002a0