

View Online at <https://aerobasegroup.com/nsn/5905-00-988-1219>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 2.8740 inches and 2.8750 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

2.859 inches

**Undercut Diameter:**

2.825 inches

**Undercut Width:**

0.0730 inches

**Body Diameter:**

3.000 inches

**Shaft Diameter:**

0.248 inches

**Shaft Length:**

0.625 inches

**Body Length:**

1.049 inches

**Overall Diameter:**

3.256 inches

**Mounting Lip Diameter:**

3.0000 inches

**Mounting Lip Depth:**

0.0930 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

Between 357.0 and 359.0

**Maximum Starting Torque:**

1.50 inch-ounces

**Maximum Running Torque:**

0.70 inch-ounces

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

5.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.10/+0.10 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

120.0 single section

**Power Dissipation Rating Per Section In Watts:**

5.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0