NSN 5905-00-988-2294

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-988-2294

| view Offilite at https://aerobasegroup.com/nsn/0303-00-300-2234 |
|---|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -25.0/+25.0 |
| Electrical Resistance: |
| 1.470 kilohms |
| Resistance Tolerance In Percent: |
| -1.000/+1.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 125.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 175.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+175.0 |
| Inclosure Method: |
| Hermetically sealed |
| Terminal Type: |
| Wire lead |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 1.000 |
| Body Diameter: |
| 0.375 inches |
| Body Length: |
| 1.062 inches |
| Power Dissipation Rating In Watts: |
| 1.000 free air |
| Style Designator: |
| Axial terminal each end |
| Test Data Document: |
| 81349-mil-prf-55182/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-prf-55182/10 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| <u></u> |
| Demilitarization: |
| No |
| Fiig: |
| A001a0 |
| Mil-std (military Standard): |
| |

Mil-prf-55182 spec.