NSN 5905-00-988-3641

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-988-3641 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.7495 inches and 0.7500 inches Pilot Length: 0.0620 inches **Overall Length:** 1.281 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.0570 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** Between 0.375 inches and 0.438 inches **Body Length:** 0.750 inches **Overall Diameter:** 1.250 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Ball **Actuator Type:** Double ended shaft **Effective Electrical Rotation In Deg Angular Rotation:** 351.5 **Maximum Starting Torque:**

0.08 inch-ounces

Maximum Running Torque:

0.08 inch-ounces

NSN 5905-00-988-3641

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.001 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
1.0 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
45.0 single section and 55.0 single section and 90.0 single section and 120.0 single section and 151.0 single section and 190.0 single
section and 230.0 single section and 270.0 single section and 340.0 single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
9 single section
Tap Location Tolerance Per Section:
-1.0/+1.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
60.0 single section
Terminal Type And Quantity:
12 turret

N/a

Shelf Life:

NSN 5905-00-988-3641

Precision Wire Wound Variable Resistor - Page 3 of 3



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A002a0