Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-988-4260

# Section Quantity:

1

Body Style:

Cylindrical

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.785 inches

#### **Body Length:**

0.421 inches

#### Actuator Type:

Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

240.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Tab

#### **Features Provided:**

Grounded contact arm

#### **Electrical Resistance Per Section:**

300.000 ohms single section

#### Rotary Actuator Travel In Angular Deg:

240.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

# Power Dissipation Rating Per Section In Watts:

1.25 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

# Actuator Travel Control Feature:

Stops

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

# Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

2 tab, solder lug

# Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 5905-00-988-4260

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0