NSN 5905-00-988-4798

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-988-4798 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.125 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.312 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 280.0 **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing

Electrical Resistance Per Section:
10.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

NSN 5905-00-988-4798

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.5 free air all sections
Resistance Tolerance Per Section In Percent:
-2.0/+2.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: