NSN 5905-00-988-6127

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-988-6127 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.5615 inches and 1.5620 inches Pilot Length: 0.0620 inches **Overall Length:** 2.206 inches **Undercut Diameter:** Between 1.620 inches and 1.625 inches **Undercut Width:** 0.0780 inches **Body Diameter:** 1.830 inches **Shaft Diameter:** Between 0.1246 inches and 0.1248 inches **Shaft Length:** Between 0.484 inches and 0.516 inches **Body Length:** 1.690 inches **Overall Diameter:** 2.048 inches **Mounting Lip Diameter:** 1.0900 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Ball **Actuator Type: Effective Electrical Rotation In Deg Angular Rotation:**

Single shaft 3600.0 **Maximum Starting Torque:** 1.00 inch-ounces **Maximum Running Torque:** 0.75 inch-ounces

NSN 5905-00-988-6127

Precision Wire Wound Variable Resistor - Page 2 of 3



Maximum Stop Torque:
200.00 inch-ounces
Shaft End Play:
0.003 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.0005 inches
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
100.0 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
1800.0 single section
Rotary Actuator Travel In Angular Deg:
3780.0
Function Conformity Tolerance Per Section:
-0.05/+0.05 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
130.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section terminal base linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-1.0/+1.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-1.0/+1.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section equation
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:

N/a

4 solder stud

Shelf Life:

NSN 5905-00-988-6127

Precision Wire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0