NSN 5905-00-988-6127

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-988-6127 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.5615 inches and 1.5620 inches Pilot Length: 0.0620 inches **Overall Length:** 2.206 inches **Undercut Diameter:** Between 1.620 inches and 1.625 inches **Undercut Width:** 0.0780 inches **Body Diameter:** 1.830 inches **Shaft Diameter:** Between 0.1246 inches and 0.1248 inches **Shaft Length:** Between 0.484 inches and 0.516 inches **Body Length:** 1.690 inches **Overall Diameter:** 2.048 inches **Mounting Lip Diameter:** 1.0900 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Ball **Actuator Type: Effective Electrical Rotation In Deg Angular Rotation:**

Single shaft 3600.0 **Maximum Starting Torque:** 1.00 inch-ounces **Maximum Running Torque:** 0.75 inch-ounces

NSN 5905-00-988-6127

Precision Wire Wound Variable Resistor - Page 2 of 3



| Maximum Stop Torque: |
|---|
| 200.00 inch-ounces |
| Shaft End Play: |
| 0.003 inches |
| Pilot Diameter Runout: |
| 0.001 inches |
| Shaft Radial Play: |
| 0.0005 inches |
| Terminal Location: |
| Longitudinally positioned on the circumference |
| Mounting Method: |
| Clamp ring |
| Electrical Resistance Per Section: |
| 100.0 kilohms single section |
| Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation: |
| 1800.0 single section |
| Rotary Actuator Travel In Angular Deg: |
| 3780.0 |
| Function Conformity Tolerance Per Section: |
| -0.05/+0.05 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 130.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -20.0/+20.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 1.0 free air single section |
| Function Conformity Per Section: |
| Single section terminal base linearity |
| Fixed Tap Quantity Per Section: |
| 1 single section |
| Tap Location Tolerance Per Section: |
| -1.0/+1.0 degrees angular rotation single section |
| Resistance Tolerance Per Section In Percent: |
| -1.0/+1.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Function Characteristic Per Section: |
| Single section equation |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 40.0 single section |
| Terminal Type And Quantity: |

N/a

4 solder stud

Shelf Life:

NSN 5905-00-988-6127

Precision Wire Wound Variable Resistor - Page 3 of 3



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A002a0