## NSN 5905-00-988-7434

**Section Quantity:** 

Rectangular w/mounting holes

**Body Style:** 

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-988-7434

. to training more
Reliability Indicator:
Not established
Overall Length:
Between 0.515 inches and 0.555 inches
Terminal Length:
0.172 inches
Overall Height:
Between 0.490 inches and 0.510 inches
Overall Width:
0.372 inches
Shaft Diameter:
Between 0.058 inches and 0.098 inches
Shaft Length:
Between 0.025 inches and 0.045 inches
Body Length:
Between 0.490 inches and 0.510 inches
Body Width:
Between 0.200 inches and 0.270 inches
Body Height:
Between 0.490 inches and 0.510 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 7200.0 and 16200.0
Center To Center Distance Between Terminals:
Between 0.195 inches and 0.205 inches
Lateral Distance Between Mounting Hole Centers:
0.520 inches
Terminal Location:
Left adjacent side single row
Mounting Method:
Terminal
Electrical Resistance Per Section:
50.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 7200.0 and 16200.0

## NSN 5905-00-988-7434

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Center To	Center	<b>Distance</b>	Between	Center	<b>Terminal</b>	And	<b>Outside</b>	Terminal:
-----------	--------	-----------------	---------	--------	-----------------	-----	----------------	-----------

Between 0.095 inches and 0.105 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.75 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

**Standard Taper Curve Per Section:** 

A single section

## **Test Data Document:**

81349-mil-r-27208 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

3 pin

**Specification Data:** 

81349-mil-r-27208/4 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0