NSN 5905-00-989-1183

Section Quantity:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

Body Style:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-989-1183

1.156 inche	9 S
Body Dian	neter:
0.500 inche	es :
Shaft Dian	neter:
0.125 inche	es es
Shaft Leng	յth։
0.500 inche	es :
Mounting	Bushing Length:
0.375 inche	es es
Body Leng	յth։
0.453 inche	?S
Overall Dia	ameter:
0.500 inche	es :
Shaft Style):
Round, slo	itted
Actuator T	ype:
Single shaf	t
Nonturn D	evice Radius:
0.245 inche	98
Screw Thr	ead Diameter:
0.250 inche	es :
Screw Thr	ead Series Designator:
Unef	
Screw Thr	eady Qty Per Inch (tpi):
32.0	
Terminal L	ocation:
Rear end	
Mounting	Method:
Locking bu	shing
Electrical I	Resistance Per Section:
2.000 meg	ohms single section
Power Dis	sipation Rating Per Section In Watts:
0.75 free a	r single section
Resistance	e Tolerance Per Section In Percent:
-20.0/+20.0	single section

NSN 5905-00-989-1183

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section		
A single section		
Terminal Type And Quantity:		
3 tab, solder lug		
Shelf Life:		
N/a		
Unit Of Measure:		
Demilitarization:		
No		

Fiig: A002a0