NSN 5905-00-989-4387

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-989-4387

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Terminal Length:
0.500 inches
Mounting Hole Diameter:
0.088 inches
Shaft Diameter:
0.115 inches
Shaft Length:
0.070 inches
Body Length:
1.250 inches
Body Width:
0.190 inches
Body Height:
0.320 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
7920.0
Center To Center Distance Between Terminals:
0.900 inches
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Unthreaded hole and terminal
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Center To Center Distance Between Center Terminal And Outside Terminal:

0.700 inches

NSN 5905-00-989-4387

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:**