NSN 5905-00-989-5081

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-989-5081

Section Quantity:					
2					
Reliability Indicator:					
Not established					
Shaft Diameter:					
Between 0.187 inches and 0.265 inches					
Shaft Length:					
Between 0.719 inches and 1.219 inches					
Shaft Style:					
Round					
Switch Type:					
Rotary					
Switch Voltage Rating In Volts:					
125.0					
Actuator Type:					
Single shaft					
Nonturn Device Location:					
At 9 oclock					
Nonturn Device Radius:					
0.487 inches					
Screw Thread Diameter:					
0.375 inches					
Screw Thread Series Designator:					
Unef					
Screw Thready Qty Per Inch (tpi):					
32.0					
Mounting Method:					
Standard bushing					
Features Provided:					
Switch					
Electrical Resistance Per Section:					
100.000 percent, rated amperes c and better industrial clears					
Power Dissipation Rating Per Section In Watts:					
1.0 free air single section					
Resistance Tolerance Per Section In Percent:					
-20.0/+20.0 1st section					
Standard Taper Curve Per Section:					
A single section					
Terminal Type And Quantity:					
6 tab, solder lug and 4 tab, solder lug					
Shelf Life:					
N/a					

NSN 5905-00-989-5081

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



	• -			
In	ıŧ	()t	Measure	•

--

Demilitarization:

No

Fiig:

A002a0