Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-990-3092

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

# **Reliability Indicator:**

Not established

## Mounting Hole Diameter:

0.090 inches

#### Shaft Diameter:

0.125 inches

- Shaft Length:
- 0.062 inches

Body Length:

1.328 inches

# Body Width:

0.344 inches

#### **Body Height:**

0.344 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

9360.0

#### Lateral Distance Between Mounting Hole Centers:

1.094 inches

#### **Mounting Facility Quantity:**

2

#### Terminal Location:

Rear end

#### **Mounting Method:**

Unthreaded hole

#### **Electrical Resistance Per Section:**

500.000 ohms single section

## Rotary Actuator Travel In Angular Deg:

9360.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-25.0/+25.0 single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section



**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

## Actuator Travel Control Feature:

Clutch

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0