NSN 5905-00-990-6805

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-990-6805

Section Quantity:
2

Reliability Indicator:
Not established

0.280 inches

Flat Height:

0.080 inches

Shaft Diameter:

First Flat Length:

Between 0.125 inches and 0.250 inches

Shaft Length:

Between 0.910 inches and 1.340 inches

Shaft Style:

Round

Actuator Type:

Dual concentric

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

5.0 percent, rated amperes c and better industrial clears

Power Dissipation Rating Per Section In Watts:

3.0 7th secondary finish

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 2nd section

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5905-00-990-6805

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



em			

No

Fiig:

A002a0