NSN 5905-00-990-8363

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-990-8363

View Online at https://aerobasegroup.com/nsn/5905-00-990-8					
Section Quantity:					
1					
Body Style:					
Cylindrical servo mounted					
Reliability Indicator:					
Not established					
Pilot Diameter:					
Between 0.6240 inches and 0.6250 inches					
Pilot Length:					
Between 0.0570 inches and 0.0670 inches					
Overall Length:					
Between 2.046 inches and 2.100 inches					
Undercut Diameter:					
Between 0.624 inches and 0.625 inches					
Undercut Width:					
Between 0.0630 inches and 0.0730 inches					
Body Diameter:					
Between 0.865 inches and 0.875 inches					
Shaft Diameter:					
0.125 inches					
Shaft Length:					
Between 0.483 inches and 0.517 inches					
Body Length:					
Between 1.563 inches and 1.583 inches					
Overall Diameter:					
1.063 inches					
Mounting Lip Diameter:					
Between 0.8650 inches and 0.8750 inches					
Mounting Lip Depth:					
Between 0.0570 inches and 0.0620 inches					
Shaft Style:					
Round					
Actuator Type:					
Single shaft					
Effective Electrical Rotation In Deg Angular Rotation:					
3600.0					
Maximum Starting Torque:					
4.00 inch-ounces					
Maximum Running Torque:					
3.00 inch-ounces					

Shaft End Play: 0.002 inches

NSN 5905-00-990-8363

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
1.5 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
180.0 single section
Rotary Actuator Travel In Angular Deg:
3780.0
Function Conformity Tolerance Per Section:
-0.05/+0.05 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-0.5/+0.5 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-1.0/+1.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section

N/a

4 solder stud

Shelf Life:

Terminal Type And Quantity:

NSN 5905-00-990-8363

Precision Wire Wound Variable Resistor - Page 3 of 3



	• •			
ın	1+	<i>(</i>)+	Measure	•

--

Demilitarization:

No

Fiig:

A002a0