

View Online at <https://aerobasegroup.com/nsn/5905-00-991-0612>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

First Flat Length:

Between 0.365 inches and 0.385 inches

Flat Height:

Between 0.115 inches and 0.135 inches

Body Diameter:

Between 0.927 inches and 0.947 inches

Shaft Diameter:

Between 0.240 inches and 0.260 inches

Shaft Length:

0.750 inches

Mounting Bushing Length:

0.375 inches

Body Length:

Between 0.865 inches and 0.885 inches

Overall Diameter:

Between 1.115 inches and 1.135 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

1.0 megohms all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 2nd section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0