NSN 5905-00-991-0751

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-991-0751 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.8740 inches and 1.8750 inches Pilot Length: 0.0620 inches **Overall Length:** 3.406 inches **Undercut Diameter:** 1.875 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 2.031 inches **Shaft Diameter:** 0.240 inches **Shaft Length:** 0.500 inches **Body Length:** 2.875 inches **Overall Diameter:** 2.391 inches **Mounting Lip Diameter:** Between 1.9900 inches and 2.0050 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round, fluted **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:**

1.50 inch-ounces

Maximum Running Torque:

1.20 inch-ounces

NSN 5905-00-991-0751

Maximum Stop Torque: 600.00 inch-ounces

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.005 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.0 percent, rated amperes c and better finish
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
1800.0 1st section
Rotary Actuator Travel In Angular Deg:
Between 3430.0 and 3790.0
Function Conformity Tolerance Per Section:
-5.00/+5.00 2nd section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-600.0/+600.0 all sections
Power Dissipation Rating Per Section In Watts:
2.5 free air all sections
Function Conformity Per Section:
All sections terminal base linearity
Fixed Tap Quantity Per Section:
7 2nd section
Tap Location Tolerance Per Section:
-1.0/+1.0 degrees angular rotation all sections
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 all sections
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
9 oclock all primaries

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

NSN 5905-00-991-0751

Precision Wire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
14 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0