NSN 5905-00-991-8855

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-991-8855 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 3.501 inches **Body Diameter:** Between 1.807 inches and 1.817 inches **Shaft Diameter:** Between 0.249 inches and 0.250 inches **Shaft Length:** Between 0.719 inches and 0.781 inches **Mounting Bushing Length:** Between 0.296 inches and 0.328 inches **Body Length:** 2.235 inches **Overall Diameter:** 2.817 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Double ended shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 3600.0 and 3604.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:** 1.50 inch-ounces **Maximum Stop Torque:** 120.00 inch-ounces **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.562 inches **Shaft End Play:** 0.00005 inches **Shaft Runout:**

0.005 inches

NSN 5905-00-991-8855

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Lateral Runout:
0.005 inches
Pilot Diameter Runout:
0.00001 inches
Shaft Radial Play:
0.002 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 3604.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:

A002a0