NSN 5905-00-992-6588

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-992-6588 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.8750 inches Pilot Length: 0.1250 inches **Overall Length:** 3.750 inches **Undercut Diameter:** 2.875 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 2.908 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.625 inches **Body Length:** 2.125 inches **Overall Diameter:** 3.298 inches **Mounting Lip Diameter:** 4.6250 inches **Mounting Lip Depth:** 0.1250 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 330.0 **Maximum Starting Torque:**

1.50 inch-ounces **Maximum Running Torque:** 1.50 inch-ounces

NSN 5905-00-992-6588

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.005 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.005 inches
Pilot Diameter Runout:
0.0015 inches
Shaft Radial Play:
0.001 inches
Fragility Factor:
Moderately delicate
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Electrical Resistance Per Section:
4.516 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.10/+0.10 single section
-0.10/+0.10 single section
-0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
-0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section
-0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -650.0/+650.0 single section
-0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -650.0/+650.0 single section Power Dissipation Rating Per Section In Watts:
-0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -650.0/+650.0 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section
-0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -650.0/+650.0 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section:
-0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -650.0/+650.0 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section: Single section proportional conformity
-0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -650.0/+650.0 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section: Single section proportional conformity Resistance Tolerance Per Section In Percent:
-0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -650.0/+650.0 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section: Single section proportional conformity Resistance Tolerance Per Section In Percent: -1.0/+1.0 single section
-0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -650.0/+650.0 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section: Single section proportional conformity Resistance Tolerance Per Section In Percent: -1.0/+1.0 single section Actuator Travel Control Feature:
-0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -650.0/+650.0 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section: Single section proportional conformity Resistance Tolerance Per Section In Percent: -1.0/+1.0 single section Actuator Travel Control Feature: Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -650.0/+650.0 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section: Single section proportional conformity Resistance Tolerance Per Section In Percent: -1.0/+1.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section:
-0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -650.0/+650.0 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section: Single section proportional conformity Resistance Tolerance Per Section In Percent: -1.0/+1.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section 360 degrees sine
-0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -650.0/+650.0 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section: Single section proportional conformity Resistance Tolerance Per Section In Percent: -1.0/+1.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section 360 degrees sine Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -650.0/+650.0 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section: Single section proportional conformity Resistance Tolerance Per Section In Percent: -1.0/+1.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section 360 degrees sine Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section

N/a

NSN 5905-00-992-6588

Precision Wire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0