NSN 5905-00-993-0357

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-993-0357

Section Quantity:
1
Body Style:
Cylindrical friction mounted
Reliability Indicator:
Not established
Overall Length:
1.412 inches
Body Diameter:
Between 0.240 inches and 0.260 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.213 inches
Body Length:
Between 0.132 inches and 0.142 inches
Overall Diameter:
Between 0.240 inches and 0.260 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
16200.0
Screw Thread Diameter:
0.216 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
28.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
16200.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

180.0 single section

NSN 5905-00-993-0357

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
0.188 in. Long bushing
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: