NSN 5905-00-993-2360

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-993-2360

View Online at https://aerobasegroup.com/nsn/5905-00-993
Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
Between 1.296 inches and 1.360 inches
Overall Height:
Between 0.312 inches and 0.344 inches
Overall Width:
Between 0.172 inches and 0.203 inches
Mounting Hole Diameter:
0.088 inches
Shaft Diameter:
Between 0.094 inches and 0.125 inches
Shaft Length:
Between 0.062 inches and 0.094 inches
Body Length:
Between 1.234 inches and 1.266 inches
Body Width:
Between 0.172 inches and 0.203 inches
Body Height:
Between 0.312 inches and 0.344 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
5.00 inch-ounces
Lateral Distance Between Mounting Hole Centers:
Between 0.995 inches and 1.005 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
100.0 kilohms single section
Rotary Actuator Travel In Angular Deg:

7920.0

NSN 5905-00-993-2360

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -70.0/+70.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:** No