## NSN 5905-00-993-3888

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-993-3888

**Section Quantity:** 

1

**Body Style:** 

Rectangular w/mounting holes/slots

**Reliability Indicator:** 

Not established

**Overall Length:** 

Between 1.280 inches and 1.344 inches

**Terminal Length:** 

Between 0.484 inches and 0.516 inches

**Overall Height:** 

Between 0.780 inches and 0.844 inches

**Overall Width:** 

Between 0.270 inches and 0.290 inches

**Mounting Hole Diameter:** 

Between 0.083 inches and 0.093 inches

**Shaft Diameter:** 

Between 0.109 inches and 0.141 inches

**Shaft Length:** 

Between 0.046 inches and 0.078 inches

**Body Length:** 

Between 1.234 inches and 1.266 inches

**Body Width:** 

Between 0.270 inches and 0.290 inches

**Body Height:** 

Between 0.296 inches and 0.328 inches

**Shaft Style:** 

Round, slotted

**Actuator Type:** 

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:** 

9000.0

**Center To Center Distance Between Terminals:** 

Between 0.690 inches and 0.710 inches

**Lateral Distance Between Mounting Hole Centers:** 

Between 0.995 inches and 1.005 inches

**Mounting Facility Quantity:** 

2

**Terminal Location:** 

Lower adjacent side two rows

**Mounting Method:** 

Terminal and unthreaded hole

## NSN 5905-00-993-3888

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.290 inches and 0.310 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0