NSN 5905-00-993-4025

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-993-4025 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.766 inches **Body Diameter:** 1.312 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.312 inches **Body Length:** 0.734 inches **Overall Diameter:** 1.312 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 352.0 **Maximum Starting Torque:** 0.70 inch-ounces **Maximum Running Torque:** 0.50 inch-ounces **Maximum Stop Torque:** 48.00 inch-ounces **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.562 inches **Shaft End Play:** 0.007 inches

Shaft Runout: 0.0025 inches

NSN 5905-00-993-4025

Precision Wire Wound Variable Resistor - Page 2 of 3



| Lateral Runout: |
|---|
| 0.003 inches |
| Pilot Diameter Runout: |
| 0.0025 inches |
| Shaft Radial Play: |
| 0.004 inches |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Rear end |
| Mounting Method: |
| Standard bushing |
| Electrical Resistance Per Section: |
| 5.0 kilohms single section |
| Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation: |
| 180.0 single section |
| Rotary Actuator Travel In Angular Deg: |
| 360.0 |
| Function Conformity Tolerance Per Section: |
| -0.50/+0.50 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 85.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 2.0 free air single section |
| Function Conformity Per Section: |
| Single section independent linearity |
| Fixed Tap Quantity Per Section: |
| 1 single section |
| Tap Location Tolerance Per Section: |
| -1.0/+1.0 degrees angular rotation single section |
| Resistance Tolerance Per Section In Percent: |
| -5.0/+5.0 single section |
| Actuator Travel Control Feature: |
| Continuous motion |
| |
| Function Characteristic Per Section: |
| Function Characteristic Per Section: Single section linear |
| |

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

NSN 5905-00-993-4025

Precision Wire Wound Variable Resistor - Page 3 of 3



| Terminal Type And Quantity: |
|-----------------------------|
| 4 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A002a0