Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-994-6908

New Online at https://aerobasegroup.com/nsn/3903-00-994-6908
Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.766 inches
Body Diameter:
Between 0.769 inches and 0.801 inches
Body Length:
0.422 inches
Overall Diameter:
Between 0.808 inches and 0.812 inches
Actuator Type:
Flush drive with slot-hole
Maximum Starting Torque:
10.00 inch-ounces
Terminal Location:
Rear end
Mounting Method:
Terminal
Features Provided:
Grounded contact arm and nonmetallic shaft
Electrical Resistance Per Section:
25.0 ohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

NSN 5905-00-994-6908

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0