NSN 5905-00-994-7233

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-994-7233

View Online at https://aerobasegroup.com/nsn/5905-00-994
Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
Between 1.300 inches and 1.340 inches
Terminal Length:
6.000 inches
Overall Height:
Between 0.300 inches and 0.320 inches
Overall Width:
Between 0.180 inches and 0.200 inches
Mounting Hole Diameter:
Between 0.088 inches and 0.098 inches
Shaft Diameter:
Between 0.100 inches and 0.130 inches
Shaft Length:
Between 0.060 inches and 0.080 inches
Body Length:
Between 1.240 inches and 1.260 inches
Body Width:
Between 0.180 inches and 0.200 inches
Body Height:
0.315 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 6120.0 and 9720.0
Maximum Starting Torque:
8.00 inch-ounces
Center To Center Distance Between Terminals:
Between 0.890 inches and 0.910 inches
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:

Rear end

NSN 5905-00-994-7233

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
1.0 megohms single section
Rotary Actuator Travel In Angular Deg:
Between 6120.0 and 9720.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.690 inches and 0.710 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0/+250.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 pin
Specification Data:
81349-mil-r-22097/2 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A00230