NSN 5905-00-994-9096

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-994-9096

Electrical Resistance:
13.000 ohms
Resistance Tolerance In Percent:
-10.000/+10.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
350.0
Inclosure Method:
Encapsulated
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
0.500 inches
Body Length:
8.250 inches
Body Width:
3.500 inches
Body Height:
Body Height: 0.500 inches
0.500 inches
0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 10.250 inches
0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 10.250 inches Power Dissipation Rating In Watts:
0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 10.250 inches Power Dissipation Rating In Watts: 170.000 free air
0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 10.250 inches Power Dissipation Rating In Watts: 170.000 free air Terminal Width:
0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 10.250 inches Power Dissipation Rating In Watts: 170.000 free air Terminal Width: 0.375 inches
0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 10.250 inches Power Dissipation Rating In Watts: 170.000 free air Terminal Width: 0.375 inches Mounting Hole Size:
0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 10.250 inches Power Dissipation Rating In Watts: 170.000 free air Terminal Width: 0.375 inches Mounting Hole Size: 0.250 inches
0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 10.250 inches Power Dissipation Rating In Watts: 170.000 free air Terminal Width: 0.375 inches Mounting Hole Size: 0.250 inches Style Designator:
0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 10.250 inches Power Dissipation Rating In Watts: 170.000 free air Terminal Width: 0.375 inches Mounting Hole Size: 0.250 inches Style Designator: Terminals one edge
0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 10.250 inches Power Dissipation Rating In Watts: 170.000 free air Terminal Width: 0.375 inches Mounting Hole Size: 0.250 inches Style Designator: Terminals one edge Shelf Life:
0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 10.250 inches Power Dissipation Rating In Watts: 170.000 free air Terminal Width: 0.375 inches Mounting Hole Size: 0.250 inches Style Designator: Terminals one edge Shelf Life: N/a
0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 10.250 inches Power Dissipation Rating In Watts: 170.000 free air Terminal Width: 0.375 inches Mounting Hole Size: 0.250 inches Style Designator: Terminals one edge Shelf Life: N/a
0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 10.250 inches Power Dissipation Rating In Watts: 170.000 free air Terminal Width: 0.375 inches Mounting Hole Size: 0.250 inches Style Designator: Terminals one edge Shelf Life: N/a Unit Of Measure:
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 10.250 inches Power Dissipation Rating In Watts: 170.000 free air Terminal Width: 0.375 inches Mounting Hole Size: 0.250 inches Style Designator: Terminals one edge Shelf Life: N/a Unit Of Measure: Demilitarization: