

View Online at <https://aerobasegroup.com/nsn/5905-00-995-0214>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

1.190 inches

**Body Diameter:**

0.505 inches

**Shaft Diameter:**

Between 0.120 inches and 0.130 inches

**Shaft Length:**

0.550 inches

**Mounting Bushing Length:**

0.220 inches

**Body Length:**

0.640 inches

**Overall Diameter:**

0.505 inches

**Shaft Style:**

Round, slotted

**Contact Arm Electrical Off Position:**

Fully ccw

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

300.0

**Maximum Stop Torque:**

48.00 inch-ounces

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

Between 0.180 inches and 0.200 inches

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear end

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

25.0 ohms single section

**Rotary Actuator Travel In Angular Deg:**

300.0

**Power Dissipation Rating Per Section In Watts:**

0.1 free air single section

**Resistance Tolerance Per Section In Percent:**

-3.0/+3.0 single section

**Actuator Travel Control Feature:**

Stops

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-50.0/+50.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0