NSN 5905-00-995-2975

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-995-2975 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.7490 inches and 0.7500 inches Pilot Length: Between 0.0570 inches and 0.0670 inches **Undercut Diameter:** Between 0.749 inches and 0.750 inches **Undercut Width:** 0.0570 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 0.375 inches **Body Length:** 1.610 inches **Mounting Lip Diameter:** Between 0.8700 inches and 0.8750 inches **Mounting Lip Depth:** Between 0.0570 inches and 0.0670 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3418.4 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:**

0.60 inch-ounces **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.001 inches

NSN 5905-00-995-2975

Precision Wire Wound Variable Resistor - Page 2 of 3



Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.0015 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
30.0 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
989.5 single section
Rotary Actuator Travel In Angular Deg:
3500.0
Function Conformity Tolerance Per Section:
-0.10/+0.10 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
12 single section
Tap Location Tolerance Per Section:
-1.7/+1.7 ohms all sections
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
105.0 single section
Terminal Type And Quantity:
15 turret
Shelf Life:
N/a
Unit Of Measure:

NSN 5905-00-995-2975

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0