

View Online at <https://aerobasegroup.com/nsn/5905-00-995-5903>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.625 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.750 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.391 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

270.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.312 inches

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Electrical Resistance Per Section:

200.0 ohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Resistance Temperature Characteristic Range Per Section In Percent:

-5.0/+5.0 -55 degrees celsius single section and -3.0/+3.0 -40 degrees celsius single section and -1.5/+1.5 0 degrees celsius single section and -1.5/+1.5 85 degrees celsius single section and -2.5/+2.5 105 degrees celsius single section and -3.5/+3.5 120 degrees celsius single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 heat sink single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0