

View Online at <https://aerobasegroup.com/nsn/5905-00-995-6015>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

Between 0.906 inches and 0.969 inches

Shaft Diameter:

Between 0.248 inches and 0.250 inches

Shaft Length:

0.875 inches

Body Length:

Between 0.453 inches and 0.516 inches

Overall Diameter:

Between 1.125 inches and 1.188 inches

Shaft Style:

Round, slotted, knurled

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Maximum Running Torque:

6.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.438 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

100.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

0.250 in. Lg bushing

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0