NSN 5905-00-995-6566



View Online at h	tps://aerobasegroup.com/nsn/5905-00-995-6566
Section Quantit	y:
1	
Body Style:	
Cylindrical bushi	ng mounted
Reliability Indic	ator:
Not established	
Overall Length:	
Between 2.906 in	nches and 3.000 inches
Body Diameter:	
Between 0.890 ii	nches and 0.922 inches
Shaft Diameter:	
Between 0.248 is	nches and 0.251 inches
Shaft Length:	
Between 2.469 ii	nches and 2.531 inches
Mounting Bush	ng Length:
Between 0.359 ii	nches and 0.391 inches
Body Length:	
Between 0.437 ii	nches and 0.469 inches
Overall Diamete	r:
1.274 inches	
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Maximum Starti	ng Torque:
6.00 inch-ounces	
Maximum Stop	Forque:
128.00 inch-ound	es
Nonturn Device	Location:

At 9 oclock

Nonturn Device Radius:

Between 0.422 inches and 0.454 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

NSN 5905-00-995-6566

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 251.0 and 318.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/4 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No.