Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-996-2123

## Section Quantity:

1

Body Style:

Rectangular

## Reliability Indicator:

Not established

## **Overall Length:**

1.100 inches

## Terminal Length:

0.500 inches

#### **Overall Height:**

0.855 inches

## Overall Width:

0.312 inches

## Shaft Diameter:

0.125 inches

# Shaft Length:

0.040 inches

Body Length:

# 1.060 inches

Body Width:

## 0.312 inches

Body Height:

## 0.355 inches

Shaft Style:

Round

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

3600.0

## Center To Center Distance Between Terminals:

0.700 inches

## **Terminal Location:**

Lower adjacent side two rows

## Mounting Method:

Terminal

## Center To Center Distance Between Terminal Rows:

0.100 inches

## **Electrical Resistance Per Section:**

5.0 kilohms single section

## **Rotary Actuator Travel In Angular Deg:**

3600.0



0.300 inches	enter Distance Between Center Terminal And Outside Terminal:
	mpurature In Deg Celsius Per Section At Zero Percent Rated Power
175.0 single	
-	e Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
	single section
	pation Rating Per Section In Watts:
1.5 free air si	
	Tolerance Per Section In Percent:
-5.0/+5.0 sing	
	avel Control Feature:
Clutch	
	mpurature In Deg Celsius Per Section At Full Rated Power:
70.0 single s	
-	per Curve Per Section:
A single sect	-
C C	aterial And Location:
Terminals sil	
Precious Ma	
Silver	
Terminal Tv	pe And Quantity:
3 pin	
Shelf Life:	
N/a	
Unit Of Mea	sure:
Demilitariza	tion:
No	
Fiig:	
A002a0	