NSN 5905-00-996-2231

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-996-2231

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.737 inches
Body Diameter:
1.750 inches
Shaft Diameter:
0.2497 inches
Shaft Length:
0.812 inches
Mounting Bushing Length:
0.312 inches
Body Length:
1.925 inches
Overall Diameter:
2.125 inches
Shaft Style:
Round
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
1.50 inch-ounces
Maximum Running Torque:
1.20 inch-ounces
Maximum Stop Torque:
750.00 inch-ounces
Nonturn Device Location:
At 6 oclock
Nonturn Device Radius:
0.562 inches
Shaft End Play:
0.00500 inches
Shaft Runout:
0.001 inches

NSN 5905-00-996-2231

Precision Wire Wound Variable Resistor - Page 2 of 3



Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.00200 inches
Shaft Radial Play:
0.003 inches
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Electrical Resistance Per Section:
50.000 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.10/+0.10 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-70.0/+70.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
7 oclock all primaries
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section

3 turret

Terminal Type And Quantity:

NSN 5905-00-996-2231

Precision Wire Wound Variable Resistor - Page 3 of 3



Shelf Li	fe:
----------	-----

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0