

View Online at <https://aerobasegroup.com/nsn/5905-00-997-1218>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.437 inches

Body Diameter:

Between 1.032 inches and 1.156 inches

Shaft Diameter:

Between 0.124 inches and 0.126 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

Between 0.344 inches and 0.390 inches

Body Length:

Between 0.468 inches and 0.656 inches

Overall Diameter:

1.515 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Starting Torque:

6.00 inch-ounces

Maximum Stop Torque:

128.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.531 inches and 0.546 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

350.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 309.0 and 320.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0/+250.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

125.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0