Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-998-4220

# Section Quantity:

1

Body Style:

Cylindrical tab/flange mounted

# **Reliability Indicator:**

Not established

## Body Diameter:

0.750 inches

#### Mounting Hole Diameter:

0.135 inches

**Body Length:** 

0.375 inches

Actuator Type:

#### Flush drive with slot-hole

## Effective Electrical Rotation In Deg Angular Rotation:

220.0

# Lateral Distance Between Mounting Hole Centers:

1.000 inches

## **Mounting Facility Quantity:**

2

# Terminal Location:

Radially positioned over less than half the circumference

#### **Mounting Method:**

Tab and unthreaded hole

#### **Electrical Resistance Per Section:**

300.0 ohms single section

#### **Rotary Actuator Travel In Angular Deg:**

220.0

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

# Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

## Standard Taper Curve Per Section:

A single section

## **Terminal Type And Quantity:**

2 tab, solder lug

# NSN 5905-00-998-4220

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0