

View Online at <https://aerobasegroup.com/nsn/5905-00-999-3805>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Overall Length:

Between 1.270 inches and 1.360 inches

Terminal Length:

Between 0.470 inches and 0.530 inches

Overall Height:

Between 0.775 inches and 0.894 inches

Overall Width:

Between 0.270 inches and 0.300 inches

Mounting Hole Diameter:

Between 0.083 inches and 0.103 inches

Shaft Diameter:

Between 0.115 inches and 0.135 inches

Shaft Length:

Between 0.040 inches and 0.090 inches

Body Length:

Between 1.230 inches and 1.270 inches

Body Width:

Between 0.270 inches and 0.300 inches

Body Height:

Between 0.305 inches and 0.364 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

7920.0

Center To Center Distance Between Terminals:

Between 0.690 inches and 0.710 inches

Lateral Distance Between Mounting Hole Centers:

Between 0.990 inches and 1.010 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side single row

Mounting Method:

Terminal and unthreaded hole

Electrical Resistance Per Section:

200.0 ohms single section

Rotary Actuator Travel In Angular Deg:

7920.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.300 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0/+250.0 single section

Power Dissipation Rating Per Section In Watts:

0.8 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0