NSN 5905-00-999-3808

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-999-3808

Section Quantity
Section Quantity:
•
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
liilength:
1.315 inches
Terminal Length:
Between 0.470 inches and 0.530 inches
liiheight:
0.835 inches
liiwidth:
Between 0.270 inches and 0.300 inches
Mounting Hole Diameter:
Between 0.083 inches and 1.003 inches
Shaft Diameter:
Between 0.115 inches and 0.135 inches
Shaft Length:
Between 0.040 inches and 0.090 inches
Body Length:
Between 1.230 inches and 1.270 inches
Body Width:
Between 0.270 inches and 0.300 inches
Body Height:
Between 0.305 inches and 0.364 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
7920.0
Center To Center Distance Between Terminals:
Between 0.690 inches and 0.710 inches
Lateral Distance Between Mounting Hole Centers:
Between 0.990 inches and 1.010 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:

Mounting Method:

Terminal and unthreaded hole

NSN 5905-00-999-3808

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
2.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.300 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single section
Power Dissipation Rating Per Section In Watts:
0.8 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0