NSN 5905-00-999-3811

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-999-3811

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Terminal Length:
0.500 inches
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
0.100 inches
Shaft Length:
0.050 inches
Body Length:
1.250 inches
Body Width:
0.290 inches
Body Height:
0.344 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
7920.0
Center To Center Distance Between Terminals:
0.700 inches
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Center To Center Distance Between Center Terminal And Outside Terminal:

0.300 inches

NSN 5905-00-999-3811

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0/+250.0 single section
Power Dissipation Rating Per Section In Watts:
0.8 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Standard Taper Curve Per Section:
A single section

3 pin

Shelf Life:

N/a

Unit Of Measure:

Terminal Type And Quantity:

Demilitarization:

No

Fiig:

A002a0