NSN 5905-00-999-7121

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-999-7121

Section Quantity:
1

Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:

0.530 inches

Shaft Diameter:

Between 0.124 inches and 0.126 inches

Shaft Length: 2.750 inches

3.440 inches **Body Diameter:**

Mounting Bushing Length:

0.265 inches

Body Length:

0.470 inches

Overall Diameter:

0.530 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Nonturn Device Location:

At 3 oclock

Nonturn Device Radius:

Between 0.240 inches and 0.250 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

100.0 ohms single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

NSN 5905-00-999-7121

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section in Percent
-10.0/+10.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0