NSN 5905-01-003-4956

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-003-4956

-200.0/+200.0 Electrical Resistance: 22.000 chms Resistance Tolerance In Percent: -2.000/42.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: -25.0 (1415.0) Inclosure Method: Encapsulated Terminal Type: Wife lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: Between 0.082 inches and 0.088 inches Body Length: Between 0.025 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similiar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical', 'average', "", etc.). Shelf Life: Na Unit Of Measure: - Demilitarization: No Filg:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
22 .000 ohms Resistance Tolerance In Percent: -2.000/42.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -25.0/4150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.025 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr22884 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Na Unit Of Measure: Demilitarization: No Filig:	-200.0/+200.0
Resistance Tolerance in Percent: -2.000/+2.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -25.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire laad Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.100 Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.205 inches and 0.281 inches Power Dissipation Rating in Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr22884 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.) Sheff Life: Na Unit Of Measure: - Demilitarization: No Filg:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -25.04+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.082 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Avail terminal each end Test Data Document: 81349-milr22884 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, inclustry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: N/a Unit Of Measure: Demilitarization: No Flig:	22.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -25.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Dlameter: Between 0.082 inches and 0.098 inches Body Dlameter: Between 0.082 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill/22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0/4150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.205 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milit 22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	-2.000/+2.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -25.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.205 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milit 22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -25.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.082 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milit22694 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -25.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: Between 0.082 inches and 0.098 inches Between 0.082 inches and 0.098 inches Body Length: Between 0.256 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill/2864 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-25.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.082 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-millr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	150.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.205 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.205 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: N/a Unit Of Measure: Demilitarization: No Fig:	-25.0/+150.0
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.205 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.205 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.205 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.205 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Reliability Failure Rate Level In Percent: 0.100 Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.205 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
Between 0.082 inches and 0.098 inches Body Length: Between 0.205 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Established
Between 0.082 inches and 0.098 inches Body Length: Between 0.205 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Failure Rate Level In Percent:
Between 0.082 inches and 0.098 inches Body Length: Between 0.205 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.100
Between 0.205 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
Between 0.205 inches and 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.082 inches and 0.098 inches
Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
O.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.205 inches and 0.281 inches
Style Designator: Axial terminal each end Test Data Document: 81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 free air
Test Data Document: 81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-milr22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
A00140	A001a0