NSN 5905-01-003-7835

Non-wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-003-7835 **Section Quantity:** 2 **Overall Length: 3.438** inches **Body Diameter:** 1.062 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.563 inches Switch Type: Rotary **Switch Voltage Rating In Volts:** 115.0 and 28.0 **Actuator Type:** Dual concentric **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 6.00 inch-ounces **Nonturn Device Location:** At 3 oclock **Nonturn Device Radius:** 0.437 inches **Shaft End Play:** 0.00300 inches **Switch Operating Position:** End of rotation **Switch Contact Arrangement:** Single pole, single throw, normally closed **Screw Thread Diameter:** 0.375 inches

Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing and clamp ring **Electrical Resistance Per Section:** 10.000 kilohms single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section

NSN 5905-01-003-7835

Non-wire Wound Variable Resistor - Page 2 of 2



Switch Current Type And Rating In Amps:
2.000 ac/dc
Standard Taper Curve Per Section:
A single section
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0